


DATA TEST NO.	W443-1274-SL	
APPLICABLE MODEL	PM3100071 A1	
SPECIFICATION	NO. OF PHASE	1 PHASE
	NO. OF POLE	4 P.
	RATED RPM.	50Hz 1300 60Hz ---
	VOLTAGE	240 V.
	CURRENT	4.80 A.
WINDING RESISTANCE (REF. 20")	OUTPUT	750 W.
	M COIL	4.41 Ω
	S COIL	10.43 Ω
	SP1 COIL	--- Ω
THERMAL PROTECTOR	SP2 COIL	--- Ω
	17AM - 150°C Refer P/N.R330-0035	
INSULATION CLASS	B	
METHOD OF COOLING	A.O.M.	
DEGREE OF PROTECTION	IP20	
WEIGHT	9.85 KGS.	




- Notes :
1. After the motor is complete, applied rust proof oil at shaft end.
 2. The tensile strength of each lead wire at least 4 Kgs.
 3. The runout of the shaft end circumference 0.10 mm.
 4. Motor can use triac control

RCT85-7504S-ODP-B02CE			
0.75kW, 4P, 4.8Amp	Cap. 25 mfd	Frame 48	
240V, 1Ph, 50Hz	Rating Cont	Mounting Nil	
Rpm 1300	Ins. Class B	Serial No. DDDMMYYXXXX	

NAMEPLATE

THIS DRAWING MAY BE USED IN WHOLE OR PART ,PROVIDED THE PIONEER MOTOR NAME & LOGO ARE VISIBLE IN ANY REPRODUCTION.



NON
SCALES

WARNING

MOTOR FITTED WITH INTERNAL AUTO RESET OVERLOAD AND MAY RESTART WITHOUT WARNING

WIRING DIAGRAM THERMALLY PROTECTED

BLUE
BLACK
BROWN
GREEN/YELLOW GROUND

DIAGRAM

FINISH:	DESCRIPTION:	REFER TO :
ASSEMBLY	MOTOR OUTLINE	ECN No.8354
ROYCECROSS	Q'TY 1	APPLICATION OUTDOOR MOTOR
		Group Code: FF85B