


DATA TEST NO.	W443-1553-SL		
APPLICABLE MODEL	PM4110382		
SPECIFICATION	NO. OF PHASE	1 PHASE	
	NO. OF POLE	4 P.	
	RATED RPM.	50Hz	1350/1160
		60Hz	---
	VOLTAGE	240 V.	
	CURRENT	0.80 A.	
OUTPUT	80 W.		
EFFICIENCY	43.2 %		
WINDING RESISTANCE	M COIL	89.88 Ω	
	S COIL	132.97 Ω	
	SP1 COIL	54.07 Ω	
	SP2 COIL	---	
(REF. 20")			
THERMAL PROTECTOR	17AM - 150°C Refer P/N.R330-0035		
INSULATION CLASS	B		
METHOD OF COOLING	A.O.M.		
DEGREE OF PROTECTION	IP54		
WEIGHT	4.28 KGS.		



**STICKER RCG**



Remark : Part No. Capacitor R330-5427

- Notes :
1. After the motor is complete, applied rust proof oil at shaft end.
  2. The tensile strength of each lead wire at least 4 Kgs.
  3. The runout of the shaft end circumference 0.16 mm.


**RCT85-804DS-TE-C02**

0.08kW , 4P , 0.8Amp	Cap. 4 mfd	Frame 48
240V , 1Ph , 50Hz	Rating Cont	Mounting Res.mt
Rpm 1350/1160	Ins. Class B	Serial No. xxxxxxxxxx

**NAMEPLATE**


**WARNING**

MOTOR FITTED WITH INTERNAL AUTO RESET OVERLOAD AND MAY RESTART WITHOUT WARNING



**DIAGRAM**

THIS DRAWING MAY BE USED IN WHOLE OR PART ,PROVIDED THE PIONEER MOTOR NAME & LOGO ARE VISIBLE IN ANY REPRODUCTION.



NON SCALES

FINISH:	DESCRIPTION:	REFER TO :
ASSEMBLY	MOTOR OUTLINE	ECN No.7495 ECN No.8005
ROYCECROSS	Q'TY 1	APPLICATION INDOOR MOTOR
		Group Code: FF85B