


100 ± 10
 Cable Multi 4 core , AWG-18 UL1015 PVC Black
 Lead wire length 850 ± 25 mm.
 Black/Brown/Blue/Green-Yellow
 With terminal # 250

DATA TEST NO.	W443-1272-SL	
APPLICABLE MODEL	PM3150022 A1	
SPECIFICATION	NO. OF PHASE	1 PHASE
	NO. OF POLE	4 P.
	RATED RPM.	50Hz 1240 60Hz ---
	VOLTAGE	240 V.
	CURRENT	7.10 A.
WINDING RESISTANCE (REF. 20")	OUTPUT	950 W.
	M COIL	3.40 Ω
	S COIL	6.56 Ω
	SP1 COIL	--- Ω
THERMAL PROTECTOR	SP2 COIL	--- Ω
		17AM - 150°C Refer P/N.R330-0035
INSULATION CLASS	B	
METHOD OF COOLING	A.O.M.	
DEGREE OF PROTECTION	IP20	
WEIGHT	11.50 KGS.	



- Notes :
1. After the motor is complete, applied rust proof oil at shaft end.
 2. The tensile strength of each lead wire at least 4 Kgs.
 3. The runout of the shaft end circumference 0.10 mm.
 4. Motor can use triac control

RCT85-9504S-ODP-B02CE			
0.95kW , 4P , 7.1Amp	Cap. 25 mfd	Frame 48	
240V , 1Ph , 50Hz	Rating Cont	Mounting Nil	
Rpm 1240	Ins. Class B	Serial No. DDMYYXXXX	

NAMEPLATE

WARNING

MOTOR FITTED WITH INTERNAL AUTO RESET OVERLOAD AND MAY RESTART WITHOUT WARNING

WIRING DIAGRAM THERMALLY PROTECTED

BLUE
BLACK
BROWN
GREEN/YELLOW GROUND

DIAGRAM

THIS DRAWING MAY BE USED IN WHOLE OR PART ,PROVIDED THE PIONEER MOTOR NAME & LOGO ARE VISIBLE IN ANY REPRODUCTION.

THIRD ANGLE PROJECTION	FINISH:	DESCRIPTION:	REFER TO :
	ASSEMBLY	MOTOR OUTLINE	ECN No.8354
NON SCALES	Q'TY	APPLICATION	Group Code:
	1	OUTDOOR MOTOR	FF85B