


CONTROL CHARACTERISTICS		
◻ MANDATORY MEASUREMENT	◊ FIT/FUNCTION SPC	△ SAFETY CHARACTERISTIC



DETAIL AT 'A' SCALE 1:1



3 CORD STREET  
 DUDLEY PARK SA 5008  
 Ph: (08) 8269 4000  
 Fax: (08) 8269 4000  
 www.roycecross.com.au

PROJECTION	DRAFTING STANDARD AS 1100	SIZE A4
ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE SPECIFIED		
TOL. 1 PLACE DECIMAL ± 0.25 ANGLE ± 0.30°		
2 PLACE DECIMAL ± 0.13		
MATL	SPEC	

TITLE			
TOTALLY ENCLOSED CAPACITOR START - 900RPM (B56 295ML)			
DRN	NL	DATE	2.12.08
CHK		APPD	
SCALE	NTS		

USED ON	FRAME 56	
KW	0.55	HP 3/4
PART NO	S.55B6CCG	AMPS 5.2
TYPE	TEFC CAP START/ CAP RUN	
CAP RUN	20	CAP START 100

BRAND	Crompton Greaves	
DRG NO	S.55B6CCG	
REV		
CODE No.		