

ROYCE CROSS GROUP

TEST REPORT

Product No. 20141229-1

Product Name Three Phase Asynchronous Motor

Model MSHE100L2-4 3.0kW

Examinee ROYCE CROSS GROUP.

Checkout Sort Periodic Test

Report Date 2015-01-04

ROYCE CROSS GROUP
TESTING CENTER

ROYCE CROSS GROUP

TEST REPORT

Report No. : 20141229-1

page of

Product Type Name	MSHE100L2-4 Three Phase Asynchronous Motor			Ser.No.	
Rated Output	3.0 kW	Rated Voltage	400 V	Rated Current	6.5 A
Rated Speed	1440 r/min	Rated Frequency	50 Hz	Insulation Class	F
Duty	S1	Protection Class	IP55	Connection	Y
Product Standard		Testing Standard	GB/T1032-2012	Production Date	
Test Item	Eligibility Value		Test Value	Test Result	
	Standard	Tolerance			
1. Stator resistance at 25°C	Ω	/	/	0.0000	/
2. No load current	A	/	/	2.89	/
3. No load current deviation	%	≤10	/	4.00	Passed
4. No load input power	W	/	/	187.6	/
5. Locked rotor current	A	/	/	42.93	/
6. Locked current/Rated current		≤7.6	+1.52	6.98	Passed
7. Locked torque	N m	/	/	53.41	/
8. Locked torque/Rated torque		≥2.3	-0.34	2.68	Passed
9. Full load current	A	/	/	6.15	/
10. Rated torque	N m	/	/	19.962	/
11. Max. torque	N m	/	/	46.04	/
12. Max. torque/Rated torque		≥2.3	-0.23	2.31	Passed
13. Min. torque	N m	/	/	34.44	/
14. Min. torque/Rated torque	N m	≥1.4	-0.21	1.73	Passed
15. Full load speed	r/min	/	/	1435.2	/
16. Output power	W	/	/	3000	/
17. Input power	W	/	/	3565.6	/
18. Efficiency	%	≥85.5	-2.18	84.14	Passed
19. Power factor		≥0.82	-0.030	0.836	Passed
20. Stator winding temp.rise	K	≤80	/	61.7	Passed
21. Ambient temperature	°C	/	/	11.85	/
22. Bearing temperature	°C	≤95	/	61.0	Passed
23. Stator core temperature	°C	/	/	52.10	/
24. Insulation resistance warmly to frameM Ω		/	/	/	/
25. Vibration	mm/s	/	/	/	/
26. Noise	dB(A)	/	/	/	/
27. High voltage test	V min	1800	/	/	/
28.					
29.					
30.					
Conclusion					

Tested by

Checked by

Formed

2015-01-04