

ROYCE CROSS GROUP

## TEST REPORT

Product No. 20150611-1

Product Name Three Phase Asynchronous Motor

Model MSHE132M1-6          4.0kW

Examinee ROYCE CROSS GROUP.

Checkout Sort Periodic Test

Report Date 2015-06-11

ROYCE CROSS GROUP  
TESTING CENTER

# ROYCE CROSS GROUP

## TEST REPORT

Report No. : 20150611-1

page of

Product Type Name	MSHE132M1-6 Three Phase Asynchronous Motor			Ser.No.	03-61
Rated Output	4.0 kW	Rated Voltage	400 V	Rated Current	8.6 A
Rated Speed	960 r/min	Rated Frequency	50 Hz	Insulation Class	F
Duty	S1	Protection Class	IP55	Connection	△
Product Standard		Testing Standard	GB/T1032-2012	Production Date	
Test Item		Eligibility Value		Test Value	Test Result
		Standard	Tolerance		
1. Stator resistance at 25℃	Ω	/	/	0.0000	/
2. No load current	A	/	/	5.25	/
3. No load current deviation	%	≤10	/	4.63	Passed
4. No load input power	W	/	/	313.1	/
5. Locked rotor current	A	/	/	63.00	/
6. Locked current/Rated current		≤6.8	+1.36	7.18	Passed
7. Locked torque	N m	/	/	81.84	/
8. Locked torque/Rated torque		≥2.0	-0.30	2.08	Passed
9. Full load current	A	/	/	8.77	/
10. Rated torque	N m	/	/	39.256	/
11. Max. torque	N m	/	/	/	/
12. Max. torque/Rated torque		/	/	/	/
13. Min. torque	N m	/	/	/	/
14. Min. torque/Rated torque	N m	/	/	/	/
15. Full load speed	r/min	/	/	973.0	/
16. Output power	W	/	/	4000	/
17. Input power	W	/	/	4678.3	/
18. Efficiency	%	≥84.6	-2.31	85.50	Passed
19. Power factor		≥0.74	-0.043	0.770	Passed
20. Stator winding temp.rise	K	≤80	/	54.2	Passed
21. Ambient temperature	℃	/	/	22.61	/
22. Bearing temperature	℃	≤95	/	56.0	Passed
23. Stator core temperature	℃	/	/	62.60	/
24. Insulation resistance warmly to frameM Ω		/	/	/	/
25. Vibration	mm/s	≤1.6	/	0.4	Passed
26. Noise	dB(A)	/	/	/	/
27. High voltage test	V min	1800	/	/	/
28.					
29.					
30.					
Conclusion					

Tested by

Checked by

Formed

2015-06-11